


ESSENTIAL SMARTBRIGHT T5 LED BATTEN

BATTEN



CE **IP20**

Features

Single piece integral design
Efficient light performance with balance brightness
Light quality combined with good energy saving

Application

Residential
Commercial
Cove Lighting

Model

Model	BN058C-6L	BN058C-6L	BN058C-9L	BN058C-12L
Size (L x W x H)	585mm x 21mm x 32mm	585mm x 21mm x 32mm	885mm x 21mm x 32mm	1185mm x 21mm x 32mm
Nominal Power	3.4W	6.5W	9.6W	13W
System Flux	300lm	600lm	900lm	1200lm

* System lumen refers to typical lumen output of NW(4000K) product, it could result less lumen in WW(3000K) or higher lumen in CW(6500K).

Specifications

Model	BN058C-6L	BN058C-6L	BN058C-9L	BN058C-12L
Input Voltage	220-240V, 50/60Hz			
Beam angle	120°			
Lifetime	15,000 hours			
CCT	3000K / 4000K / 6500K			
Weight (kg)	N/A	N/A	N/A	N/A
IP Rating	IP20			
Power Factor	> 0.5			
Color Index	> 70			
Materials & Finishing	Polycarbonate cover, White finishing			
Operating Temp.	- 40 °C < Ta < + 50 °C			
Mounting Type	Surface Mounting			
Standard	CE, RoHS			

* Power cable & link cable accessories need to be purchased separately, general power cable / link cable connector is not compatible.