


SMARTBRIGHT LUXLINE BATTEN G2 (T5)

BATTEN



CE IP20

Features

Comfortable light with excellent uniformity
Excellent light quality. CRI \geq 80
30,000 hours lifetime

Application

Parking, parterres, trees,
boscage
Security
Warehouses

Model

Model	BN098C LED8	BN098C LED12	BN098C LED13	BN098C LED16
Size (L)	600mm	900mm	1000mm	1200mm
Nominal Power	6.3W	9.4W	10.2W	12.5W
System Flux	800lm	1,200lm	1,300lm	1,600lm

* System lumen refers to typical lumen output of NW(4000K) product, it could result less lumen in WW(3000K) or higher lumen in CW(6500K).

Specifications

Model	BN098C LED8	BN098C LED12	BN098C LED13	BN098C LED16
Input Voltage	220-240V, 50/60Hz			
Beam angle	120°			
Lifetime	30,000 hours			
CCT	2700K / 3000K / 4000K / 6500K			
Weight (kg)	N/A	N/A	N/A	N/A
IP Rating	IP20			
Power Factor	> 0.9			
Color Index	> 80			
Materials & Finishing	Polycarbonate cover, White finishing			
Operating Temp.	-			
Mounting Type	Surface Mounting			
Standard	CE, RoHS			