


SMARTBRIGHT SUSPENDED

BATTEN



CE IP20

Features

Stylish product look & feel
System efficacy up to 90 lm/W
Visual Comfort with enough light output

Application

Office
Retail
Open Area

Model

Model	RC095V LED13S	RC095V LED15S	RC095V LED26S	RC095V LED30S
Size (L x W x H)	600mm x 70mm x 65mm	600mm x 120mm x 65mm	1200mm x 70mm x 65mm	1200mm x 120mm x 65mm
Nominal Power	14W	17W	28W	34W
System Flux	1,300lm	1,500lm	2,600lm	3,000lm

* System lumen refers to typical lumen output of NW(4000K) product, it could result less lumen in WW(3000K) or higher lumen in CW(6500K).

Specifications

Model	RC095V LED13S	RC095V LED15S	RC095V LED26S	RC095V LED30S
Input Voltage	220-240V, 50/60Hz			
Beam angle	120°			
Lifetime	25,000 hours			
CCT	3000K / 4000K / 6500K			
Weight (kg)	0.939 kg	1.079 kg	1.659 kg	1.919 KG
IP Rating	IP20			
Power Factor	> 0.9			
Color Index	> 80			
Materials & Finishing	Aluminium extruded housing, Black / Grey finished			
Operating Temp.	-10 °C to + 35 °C			
Mounting Type	Suspended			
Standard	CE, RoHS			