


ESS. SMARTBRIGHT SPOTLIGHT



Features

Mono green light option
 Beam angle options
 15,000 hrs lifetime

Application

Landscape, architectural lighting
 Parking, parterres, trees, bosage
 Security

Model

Model	BGP150 LED250	BGP150 LED400	BGP150 LED520
Size (D x H x W x L)	60 mm x 80mm x 77mm x 131mm	60 mm x 80mm x 77mm x 131mm	60 mm x 80mm x 77mm x 131mm
Nominal Power	3W	6W	8W
System Flux	250lm	400lm	520lm

* System lumen refers to typical lumen output of NW(4000K) product, it could result less lumen in WW(3000K) or higher lumen in CW(6500K).

Specifications

Model	BGP150 LED250	BGP150 LED400	BGP150 LED520
Input Voltage	220-240V, 50/60Hz		
Beam angle	25° / 40°		
Lifetime	15,000 hours		
CCT	3000K / 4000K		
Weight (kg)	0.38 kg	0.38 kg	0.38 kg
IP Rating	IP65		
Power Factor	> 0.5		
Color Index	> 80		
Materials & Finishing	Housing : Black		
Operating Temp.	- 40 °C to + 50 °C		
Mounting Type	Bracket / Spike		
Standard	CE		